

| TÁN HÀN VUÔNG DIN 928   |  |  |                 |          |  |  |
|---|--|--|-----------------|----------|--|--|
|  |  |  | Mã vật liệu (V) |          |  |  |
|   |  |  | D10             | Thép 8.8 |  |  |
|   |  |  | H00             | Inox 304 |  |  |

| Mã hàng     | M x Bước ren | Vật liệu (V) | h (mm) |     | m (mm) | s (mm) |
|-------------|--------------|--------------|--------|-----|--------|--------|
|             |              |              | Min    | Max |        |        |
| N09M0401(V) | M4 x 0.7     | D10 - H00    | 0.5    | 0.7 | 3.5    | 7      |
| N09M0501(V) | M5 x 0.8     |              | 0.7    | 0.9 | 4.2    | 9      |
| N09M0601(V) | M6 x 1.0     |              | 0.7    | 0.9 | 5      | 10     |
| N09M0801(V) | M8 x 1.25    |              | 0.9    | 1.1 | 6.5    | 14     |
| N09M1001(V) | M10 x 1.5    |              | 1.1    | 1.3 | 8      | 17     |
| N09M1201(V) | M12 x 1.75   |              | 1.3    | 1.5 | 9.5    | 19     |

| TÁN KEO HỆ INCH DIN 985  |  |  |                 |                 |  |  |
|--|--|--|-----------------|-----------------|--|--|
|  |  |  | Mã vật liệu (V) |                 |  |  |
|  |  |  | D20             | Thép 8.8 mạ kẽm |  |  |
|  |  |  | H00             | Inox 304        |  |  |

| Mã hàng     | Kích thước ren (d) | Số răng/1 Inch | S (Inch) |       | h (Inch) |       | e (Inch) |
|-------------|--------------------|----------------|----------|-------|----------|-------|----------|
|             |                    |                | Min      | Max   | Min      | Max   | Min      |
| N03S1201(V) | 1/2"-13 UNC        | 13             | 0.861    | 0.879 | 0.688    | 0.718 | 0.969    |
| N03S1202(V) | 1/2"-20 UNF        | 20             | 0.861    | 0.879 | 0.688    | 0.718 | 0.969    |
| N03S1401(V) | 1/4"-20 UNC        | 20             | 0.489    | 0.506 | 0.36     | 0.39  | 0.556    |
| N03S1402(V) | 1/4"-28 UNF        | 28             | 0.489    | 0.506 | 0.36     | 0.39  | 0.556    |
| N03S3401(V) | 3/4"-10 UNC        | 10             | 1.231    | 1.255 | 0.985    | 1.015 | 1.382    |
| N03S3402(V) | 3/4"-16 UNF        | 16             | 1.231    | 1.255 | 0.985    | 1.015 | 1.382    |
| N03S3801(V) | 3/8"-16 UNC        | 16             | 0.675    | 0.691 | 0.532    | 0.562 | 0.763    |
| N03S3802(V) | 3/8"-24 UNF        | 24             | 0.675    | 0.691 | 0.532    | 0.562 | 0.763    |
| N03S5801(V) | 5/8"-11 UNC        | 11             | 1.045    | 1.067 | 0.844    | 0.874 | 1.175    |
| N03S5802(V) | 5/8"-18 UNF        | 18             | 1.045    | 1.067 | 0.844    | 0.874 | 1.175    |
| N03S5161(V) | 5/16"-18 UNC       | 18             | 0.551    | 0.566 | 0.423    | 0.453 | 0.556    |
| N03S5162(V) | 5/16"-24 UNF       | 24             | 0.551    | 0.566 | 0.423    | 0.453 | 0.556    |
| N03S7161(V) | 7/16"-14 UNC       | 14             | 0.736    | 0.754 | 0.579    | 0.609 | 0.829    |
| N03S7162(V) | 7/16"-20 UNF       | 20             | 0.736    | 0.754 | 0.579    | 0.609 | 0.829    |
| N03S9161(V) | 9/16"-12 UNC       | 12             | 0.922    | 0.942 | 0.782    | 0.812 | 1.037    |
| N03S9162(V) | 9/16"-18 UNF       | 18             | 0.922    | 0.942 | 0.782    | 0.812 | 1.037    |